

### Danger



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name : Oxygen (refrigerated); Gourmet O-E948; Diveline O

SDS no : RS-O2-097B

Other means of identification

CAS no. : 7782-44-7

EC no. : 231-956-9

Index no. : 008-001-00-8

REACH no. : Listed in Annex IV / V REACH, exempted from registration.

Chemical formula : O<sub>2</sub>

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use.  
Test gas / Calibration gas. Chemical reaction / Synthesis. Laboratory use.  
Shield gas for welding processes.  
Use for manufacture of electronic / photovoltaic components.  
Laser gas. Welding, cutting, heating and brazing.  
Water treatment.  
Food applications.  
Medical applications.

Uses advised against : Consumer use.  
Uses other than those listed above are not supported, contact your supplier for more information on other uses.  
Attention: These products must not be applied to humans or animals unless they are expressly designated as medical or medicinal gases!

### 1.3. Details of the supplier of the safety data sheet

Messer Tehnogas AD Beograd

Banjicki put no. 62

11090 Belgrade, Serbia

Telephone: +381 11 35 37 200 Fax: +381 11 35 37 291

e-mail: [postoffice@messer.rs](mailto:postoffice@messer.rs)

Web: [www.messer.rs](http://www.messer.rs)

#### **Person responsible for the safety data sheet:**

Tamara Ječmenica, Chemicals Advisor

Telephone: +381 65 35 37 785

e-mail: [sds@messer.rs](mailto:sds@messer.rs)

### 1.4. Emergency telephone number

Emergency telephone number : Poison Control Center, VMA

Crnotravska 17, Belgrade Serbia

Tel. : +381(0) 11 360 8440 (24h)

# Safety Data Sheet

## Oxygen (refrigerated)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Reference number: RS-02-097B

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards	Oxidising Gases, Category 1	H270
	Gases under pressure : Refrigerated liquefied gas	H281

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)	:	 
		GHS03 GHS04

Signal word (CLP)

: Danger

Hazard statements (CLP)

: H270 - May cause or intensify fire; oxidiser.

H281 - Contains refrigerated gas; may cause cryogenic burns or injury.

Precautionary statements (CLP)

- Prevention : P220 - Keep away from clothing and other combustible materials.  
P244 - Keep valves and fittings free from oil and grease.  
P282 - Wear cold insulating gloves and either face shield or eye protection.
- Response : P336 + P315 - Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice.  
P370 + P376 - In case of fire: Stop leak if safe to do so.
- Storage : P403 - Store in a well-ventilated place.

#### 2.3. Other hazards

Not classified as PBT or vPvB. Not classified as PMT or vPvM.

The substance / mixture has no endocrine disrupting properties.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP] ATE, EUH-statements, M-Factors
Oxygen (refrigerated)	CAS no.: 7782-44-7 EC no.: 231-956-9 Index no.: 008-001-00-8 REACH no.: *1	≤ 100	Ox. Gas 1, H270 Press. Gas (Ref. Liq.), H281

Contains no other components or impurities which will influence the classification of the product.

\*1: Listed in Annex IV / V REACH, exempted from registration.

\*3: Registration not required: Substance manufactured or imported < 1t/y.

#### 3.2. Mixtures

Not applicable

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Maintain an open airway. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact : Carefully remove contaminated clothing. In case of frostbite spray with water for at least 15 minutes. Do not use hot water! Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove any contact lenses. Obtain medical assistance.
- Ingestion : Ingestion is not considered a potential route of exposure.

#### 4.2. Most important symptoms and effects, both acute and delayed

Continuous inhalation of concentrations higher than 75% may cause nausea, dizziness, respiratory difficulty and convulsion. See section 11.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Take first aid measures. Loosen tight clothing, such as a collar, tie or belt. Place the unconscious person in a lateral position. Seek medical attention.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog. Product does not burn, use fire control measures appropriate for the surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

- Specific hazards : Supports combustion. Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : None.

#### 5.3. Advice for firefighters

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.  
If possible, stop flow of product.  
Use water spray or fog to knock down fire fumes if possible.  
If leaking do not spray water onto container. Water surrounding area (from protected position) to contain fire.  
Move containers away from the fire area if this can be done without risk.
- Special protective equipment for fire fighters : Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.  
Standard EN 469 - Protective clothing for firefighters.  
Standard EN 659 - Protective gloves for firefighters.  
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

### SECTION 6: Accidental release measures

#### **6.1. Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel

- : Act in accordance with local emergency plan.
- Try to stop release.
- Evacuate area.
- Eliminate ignition sources.
- Ensure adequate air ventilation.
- Use protective clothing.
- See section 8 of the SDS for more information on personal protective equipment.

For emergency responders

- : Monitor concentration of released product.
- Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
- See section 5.3 of the SDS for more information.

#### **6.2. Environmental precautions**

- Try to stop release.
- Liquid spillages can cause embrittlement of structural materials.

#### **6.3. Methods and material for containment and cleaning up**

- Ventilate area.

#### **6.4. Reference to other sections**

- See also sections 8 and 13.

### SECTION 7: Handling and storage

#### **7.1. Precautions for safe handling**

Safe use of the product

- : The product must be handled in accordance with good industrial hygiene and safety procedures.
- Do not eat, drink or smoke while working with the product.
- Wash hands after use. Keep equipment free from oil and grease!
- Keep equipment free from oil and grease. For more guidance, refer to the EIGA Doc. 33 - Cleaning of Equipment for Oxygen Service downloadable at <http://www.eiga.eu>
- Only experienced and properly instructed persons should handle gases under pressure.
- Wear personal protective equipment (See section 8).
- Consider pressure relief device(s) in gas installations.
- Ensure the complete gas system was (or is regularly) checked for leaks before use.
- Use only oxygen approved lubricants and oxygen approved sealings. Use no oil or grease!
- Use only with equipment cleaned for oxygen service and rated for container pressure.
- Use only properly specified equipment which is suitable for this product, its supply pressure and temperature.
- Contact your gas supplier if in doubt.
- Avoid suck back of water, acid and alkalis.
- Do not breathe gas.
- Avoid release of product into work area.

## Oxygen (refrigerated)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Reference number: RS-O2-097B

Safe handling of the gas receptacle

- : Refer to supplier's container handling instructions.
- Protect containers from physical damage; do not drag, roll, slide or drop.
- When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
- Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
- If the protection cap is too tight, remove it with adjustable wrench.
- Never insert sharp objects into the cavities of the cap, this can lead to damage to the valve and leakage. Open valve slowly to avoid pressure shock.
- If user experiences any difficulty operating valve discontinue use and contact supplier.
- Never attempt to repair or modify container valves or safety relief devices.
- Damaged valves should be reported immediately to the supplier.
- Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
- Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another.
- Never use direct flame or electrical heating devices to raise the pressure of a container.
- Do not allow backfeed into the container. Suck back of water into the container must be prevented.
- Do not remove or deface labels provided by the supplier for the identification of the content of the container.

### **7.2. Conditions for safe storage, including any incompatibilities**

- Segregate from flammable gases and other flammable materials in store.
- Observe all regulations and local requirements regarding storage of containers.
- Containers should not be stored in conditions likely to encourage corrosion.
- Container valve guards or caps should be in place.
- Containers should be stored in the vertical position and properly secured to prevent them from falling over.
- Stored containers should be periodically checked for general condition and leakage.
- Keep container below 50°C in a well ventilated place.
- Store containers in location free from fire risk and away from sources of heat and ignition.
- Keep away from combustible materials.
- For more guidance on the safe storage of liquid oxygen, liquid nitrogen or liquid argon, refer to EIGA Doc.224 "Static Vacuum Insulated Cryogenic Vessels Operation and Inspection", downloadable at <http://www.eiga.eu> and consult your supplier.

### **7.3. Specific end use(s)**

None.

## **SECTION 8: Exposure controls/personal protection**

### **8.1. Control parameters**

OEL (Occupational Exposure Limits)	: None available.
DNEL (Derived-No Effect Level)	: None available.
PNEC (Predicted No-Effect Concentration)	: None available.

### **8.2. Exposure controls**

#### **8.2.1. Appropriate engineering controls**

Provide adequate general and local exhaust ventilation.  
Systems under pressure should be regularly checked for leakages.  
Avoid oxygen rich (>23,5%) atmospheres.  
Gas detectors should be used when oxidising gases may be released.  
Consider the use of a work permit system e.g. for maintenance activities.

#### **8.2.2. Individual protection measures, e.g. personal protective equipment**

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected.

- Eye/face protection

: Wear goggles and a face shield when transfilling or breaking transfer connections.  
Standard EN 166 - Personal eye-protection - specifications.  
[Standard EN ISO 16321-1 - Eye and face protection for occupational use Part 1: General requirements](#).

- Skin protection

- Hand protection

: Wear working gloves when handling gas containers.  
Standard EN 388 - Protective gloves against mechanical risks, performance level 1 or higher.  
Recommended types include wrist gloves from leather or synthetic material with equivalent performance, fabric gloves, fabric gloves with leather palms.  
Wear cold insulating gloves when transfilling or breaking transfer connections.  
Standard EN 511 - Cold insulating gloves, performance level 1 or higher. Recommended types include insulated gauntlets or gloves specifically selected to prevent liquid penetration and ingress of cryogenic liquids and to provide mechanical resistance.

- Other

: Consider the use of flame resistant safety clothing.  
Standard EN ISO 14116 - Limited flame spread materials.  
Wear safety shoes while handling containers.  
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

- Respiratory protection

: None necessary.  
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.

- Thermal hazards

: None in addition to the above sections.

#### **8.2.3. Environmental exposure controls**

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

## **SECTION 9: Physical and chemical properties**

### **9.1. Information on basic physical and chemical properties**

Appearance

- Physical state at 20°C / 101.3kPa : Gas.  
- Colour : Bluish liquid.

Odour

: Odourless.

Melting point / Freezing point

: -219 °C

Boiling point

: -183 °C

Flammability	: Non flammable.
Lower explosion limit	: Not applicable.
Upper explosion limit	: Not applicable.
Flash point	: Not applicable for gases and gas mixtures.
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
pH	: Not applicable for gases and gas mixtures.
Viscosity, kinematic	: No reliable data available.
Water solubility [20°C]	: 39 mg/l
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for inorganic products.
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Density and/or relative density	: Not applicable for gases and gas mixtures.
Relative vapour density (air=1)	: 1.1
Particle characteristics	: Not applicable for gases and gas mixtures. Nanoforms are not relevant for gases and gas mixtures.

**9.2. Other information****9.2.1. Information with regard to physical hazard classes**

Explosion limits	: Not known.
Oxidising properties	: Oxidiser.
- Coefficient of oxygen equivalency (Ci)	: 1
Critical temperature [°C]	: -118 °C

**9.2.2. Other safety characteristics**

Molar mass	: 32 g/mol
------------	------------

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No reactivity hazard other than the effects described in sub-sections below.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Risk of explosion if spilt on organic structural materials (e.g. wood or asphalt).  
Violently oxidises organic material.

**10.4. Conditions to avoid**

Avoid moisture in installation systems.

**10.5. Incompatible materials**

Keep equipment free from oil and grease. Consider the potential toxicity hazard due to the presence of chlorinated or fluorinated polymers in high pressure (> 30 bar) oxygen lines in case of combustion. Consult supplier for specific recommendations. May react violently with combustible materials. May react violently with reducing agents. Materials such as carbon steel, low alloy carbon steel and plastic become brittle at low temperatures and are subject to failure. Use appropriate materials compatible with the cryogenic conditions present in refrigerated liquefied gas systems. For additional information on compatibility refer to ISO 11114.

### **10.6. Hazardous decomposition products**

None.

## **SECTION 11: Toxicological information**

### **11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

<b>Acute toxicity</b>	: No known toxicological effects from this product.
<b>Skin corrosion/irritation</b>	: No known effects from this product.
<b>Serious eye damage/irritation</b>	: No known effects from this product.
<b>Respiratory or skin sensitisation</b>	: No known effects from this product.
<b>Germ cell mutagenicity</b>	: No known effects from this product.
<b>Carcinogenicity</b>	: No known effects from this product.
<b>Toxic for reproduction : Fertility</b>	: No known effects from this product.
<b>Toxic for reproduction : unborn child</b>	: No known effects from this product.
<b>STOT-single exposure</b>	: No known effects from this product.
<b>STOT-repeated exposure</b>	: No known effects from this product.
<b>Aspiration hazard</b>	: Not applicable for gases and gas mixtures.

### **11.2. Information on other hazards**

Other information	: The substance / mixture has no endocrine disrupting properties.
-------------------	---

## **SECTION 12: Ecological information**

### **12.1. Toxicity**

Assessment	: No ecological damage caused by this product.
EC50 48h - Daphnia magna [mg/l]	: No data available.
EC50 72h - Algae [mg/l]	: No data available.
LC50 96 h - Fish [mg/l]	: No data available.

### **12.2. Persistence and degradability**

Assessment	: No ecological damage caused by this product.
------------	--

### **12.3. Bioaccumulative potential**

Assessment	: No ecological damage caused by this product.
------------	--

### **12.4. Mobility in soil**

Assessment	: No ecological damage caused by this product.
------------	--

### **12.5. Results of PBT and vPvB assessment**

Assessment	: Not classified as PBT or vPvB.
------------	----------------------------------

### **12.6. Endocrine disrupting properties**

Assessment	: The substance/mixture has no endocrine disrupting properties.
------------	---

### **12.7. Other adverse effects**

Other adverse effects	: Can cause frost damage to vegetation.
Effect on the ozone layer	: No effect on the ozone layer.
Effect on global warming	: None.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Contact supplier if guidance is required.

Ensure that the emission levels from local regulations or operating permits are not exceeded.

Refer to the EIGA code of practice Doc.30/21 "Disposal of Gases", downloadable at <http://www.eiga.eu> for more guidance on suitable disposal methods.

Do not discharge into any place where its accumulation could be dangerous.

May be vented to atmosphere in a well ventilated place.

Return unused product in original container to supplier.

List of hazardous waste codes (from Commission Delegated Decision (EU) 2025/934 of 5 March 2025 amending Decision 2000/532/EC)

: 16 05 04 \*: Gases in pressure containers (including halons) containing hazardous substances.

#### 13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

### SECTION 14: Transport information

#### 14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN

UN-No. : 1073


#### 14.2. UN proper shipping name

**Transport by road/rail/inland waterways (ADR/RID/ADN)** : OXYGEN, REFRIGERATED LIQUID

**Transport by air (ICAO-TI / IATA-DGR)** : Oxygen, refrigerated liquid

**Transport by sea (IMDG)** : OXYGEN, REFRIGERATED LIQUID

#### 14.3. Transport hazard class(es)



2.2 : Non flammable, non-toxic gases.

5.1 : Oxidizing substances.

#### **Transport by road/rail/inland waterways (ADR/RID/ADN)**

Class : 2

Classification code : 30

Hazard identification number : 225

Tunnel Restriction : C/E - Tank carriage : Passage forbidden through tunnels of category C, D and E. Other carriage : Passage forbidden through tunnels of category E

#### **Transport by sea (IMDG)**

Class / Div. (Sub. risk(s)) : 2.2 (5.1)

Emergency Schedule (EmS) - Fire : F-C

Emergency Schedule (EmS) - Spillage : S-W

# Safety Data Sheet

## Oxygen (refrigerated)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Reference number: RS-O2-097B

### **14.4. Packing group**

Transport by road/rail/inland waterways : Not applicable.  
 (ADR/RID/ADN)

Transport by air (ICAO-TI / IATA-DGR) : Not applicable.

Transport by sea (IMDG) : Not applicable.

### **14.5. Environmental hazards**

Transport by road/rail/inland waterways : None.  
 (ADR/RID/ADN)

Transport by air (ICAO-TI / IATA-DGR) : None.

Transport by sea (IMDG) : None.

### **14.6. Special precautions for user**

#### **Packing Instruction(s)**

Transport by road/rail/inland waterways : P203.  
 (ADR/RID/ADN)

Transport by air (ICAO-TI / IATA-DGR)

- Passenger and Cargo Aircraft : Forbidden.
- Cargo Aircraft only : Forbidden.

Transport by sea (IMDG) : P203.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment.  
 Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.  
 Before transporting product containers:
 

- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.

### **14.7. Maritime transport in bulk according to IMO instruments**

Not applicable.

## SECTION 15: Regulatory information

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### **RS Regulations**

Pravilnik o ograničenjima i zabranama proizvodnje, stavljanja : None.  
 u promet i korišćenja hemikalija ("Sl. Glasnik RS", br. 90/13,  
 25/15, 2/16, 44/17, 36/18, 9/20, 57/22, 29/24 i 90/25)  
 Pravilnik o izvozu i uvozu određenih opasnih hemikalija („Sl. glasnik RS“ br. 93/23 i 78/25)  
 Zakon o kontroli opasnosti od velikih udesa koji uključuju : Covered.  
 opasne supstance ("Sl. Glasnik RS", br. 94/24)

<b>Pravilnik o Listi opasnih supstanci, vrstama i količinama opasnih supstanci i kriterijumima za razvijanje kompleksa u kompleksu nižeg reda i kompleksa višeg reda ("Sl. glasnik RS", br. 28/25)</b>	<b>Qualifying quantity (tonnes)</b>	
	<b>Lower-tier</b>	<b>Upper-tier</b>
Oxygen	200	2000

# Safety Data Sheet

## Oxygen (refrigerated)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Reference number: RS-O2-097B

### EU Regulations

Restrictions on use : None.

Other information, restriction and prohibition regulations : Not listed on the PIC list (Regulation EU 649/2012).  
Not listed on the POP list (Regulation EU 2019/1021).

Seveso Directive : 2012/18/EU (Seveso III) : Covered.

Seveso III Deo II (Nazivi opasnih supstanci)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
Oxygen	200	2000

### 15.2. Chemical safety assessment

A CSA does not need to be carried out for this product.

## SECTION 16: Other information

Indication of changes : In Section 1, the Safety Data Sheet is supplemented with information about details of the supplier of the safety data sheet.  
In Section 2, the Safety Data Sheet is supplemented with other hazards.  
In Section 8, the Safety Data Sheet is supplemented with information about personal protection.  
In Section 12, the Safety Data Sheet is supplemented with other adverse effects.  
In Section 13, the Safety Data Sheet is supplemented with information about waste treatment methods.  
In Section 15, the Safety Data Sheet is supplemented with regulatory information.

Abbreviations and acronyms : ADN - International Carriage of Dangerous Goods by Inland Waterways  
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
ATE - Acute Toxicity Estimate  
CAS - Chemical Abstract Service number  
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008  
CSA - Chemical Safety Assessment  
DNEL - Derived No Effect Levels  
EINECS - European Inventory of Existing Commercial Chemical Substances  
EC- European Community number  
EIGA - European Industrial Gases Association  
EN - European Standard  
IATA - International Air Transport Association  
ICAO - International Civil Aviation Organization  
IMDG - International Maritime Dangerous Goods  
IMO - International Maritime Organization  
LC50 - Lethal Concentration to 50 % of a test population  
LD50 - Lethal Dose 50%  
LEL - Lower Explosive Limit  
OEL - Occupational exposure limits  
PBT - Persistent, Bioaccumulative and Toxic  
PMT - Perzistentno, mobilno i toksično .  
PNEC - Predicted No Effect Concentration  
PPE - Personal Protection Equipment  
PROC - Procesna kategorija (Process category).

# Safety Data Sheet

## Oxygen (refrigerated)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Reference number: RS-02-097B

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

RMM - Risk Management Measures

STOT - RE - Specific Target Organ Toxicity - Repeated Exposure

STOT - SE - Specific Target Organ Toxicity - Single Exposure

STEL - Short Term Exposure Limit

TWA - 8-hour total weight average

UEL - Upper explosive limit

UFI - Unique Formula Identifier

UN - United Nations

vPvB - Very Persistent and Very Bioaccumulative

vPvM - veoma perzistentno i veoma mobilno.

WGK - Water Hazard Class

Training advice

: Receptacle under pressure. Ensure operators understand the hazard of oxygen enrichment.

Further information

: Classification in accordance with the procedures and calculation methods of Regulation (EC)

1272/2008 (CLP). Key literature references and sources of data are maintained in EIGA doc 169 :

'Classification and Labelling Guide', downloadable at <http://www.eiga.eu>

Full text of H- and EUH-statements	
H270	May cause or intensify fire; oxidiser.
H281	Contains refrigerated gas; may cause cryogenic burns or injury.
Ox. Gas 1	Oxidising Gases, Category 1
Press. Gas (Ref. Liq.)	Gases under pressure : Refrigerated liquefied gas

### DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press.

Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

**End of document**