

## Danger



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name	: Propane-butane gas; LPG
SDS no.	: RS-C3H8-C4H10-01
Other means of identification	Liquefied Petroleum Gas
CAS no.	: 68476-85-7
EC no.	: 270-704-2
Index no.	: 649-202-00-6
REACH no.	: 01-2119486944-21

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	: Industrial and professional uses. Perform risk assessment prior to use. Test gas/Calibration gas. Chemical reaction / Synthesis. Use as a fuel. Fuel gas for welding, cutting, heating, brazing and soldering applications.
Uses advised against	: Consumer use. Uses other than those listed above are not supported, contact your supplier for more information on other uses.

### 1.3. Details of the supplier of the safety data sheet

Messer Tehnogas AD Beograd  
Banjicki put no. 62  
11090 Belgrade, Serbia  
Telephone: +381 11 35 37 200 Fax: +381 11 35 37 291  
e-mail: [postoffice@messer.rs](mailto:postoffice@messer.rs)  
Web: [www.messer.rs](http://www.messer.rs)

#### Person responsible for the safety data sheet:

Tamara Ječmenica, Chemicals Advisor

Telephone: +381 65 35 37 785

e-mail: [sds@messer.rs](mailto:sds@messer.rs)

### 1.4. Emergency telephone number

Emergency telephone number	: Poison Control Center, VMA Crnotravska 17, Belgrade Serbia Tel. : +381(0) 11 360 8440 (24h)
----------------------------	---

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards	Flammable gases, Category 1A	H220
------------------	------------------------------	------

# Safety Data Sheet

## Propane-butane gas; LPG

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Reference number: RS-C3H8-C4H10-01

Gases under pressure : Liquefied gas

H280

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS04

Signal word (CLP)

: Danger

Hazard statements (CLP)

: H220 - Extremely flammable gas.

H280 - Contains gas under pressure; may explode if heated.

Precautionary statements (CLP)

- Prevention : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Response : P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
- Response : P381 - In case of leakage, eliminate all ignition sources.
- Storage : P403 - Store in a well-ventilated place.

### 2.3. Other hazards

Asphyxiant in high concentrations. Contact with liquid may cause cold burns/frostbite.

These high concentrations are within the flammability range.

Not classified as PBT or vPvB. Not classified as PMT or vPvM.

The substance/mixture has no endocrine disrupting properties.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP] ATE, EUH-statements, M-Factors
Petroleum gases, liquefied	CAS no.: 68476-85-7 EC no.: 270-704-2 Index no.: 649-202-00-6 REACH no.: 01-2119485911-31	≤ 100	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
1-3 butadiene	CAS no. : 106-99-0 EC no. : 203-450-8 Indeks no. : 601-004-00-0 REACH no. : 01-2119474691-32	<0,1	Flam. Gas 1A, H220 Press. Gas (Liq.), H280 Carc. 1A, H350 Muta. 1B, H340

Contains no other components or impurities which will influence the classification of the product.

### 3.2. Mixtures

Not applicable

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Maintain an open airway. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact : Carefully remove contaminated clothing. In case of frostbite spray with water for at least 15 minutes. Do not use hot water! Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove any contact lenses. Obtain medical assistance.
- Ingestion : Ingestion is not considered a potential route of exposure.

#### 4.2. Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. See section 11.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Take first aid measures. Loosen tight clothing, such as a collar, tie or belt.  
Place the unconscious person in a lateral position. Seek medical attention.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog. Carbon dioxide. Dry powder.  
Shutting off the source of the gas is the preferred method of control.  
Be aware of the risk of formation of static electricity with the use of CO<sub>2</sub> extinguishers. Do not use them in places where a flammable atmosphere may be present.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : Carbon monoxide.

#### 5.3. Advice for firefighters

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product.  
Use water spray or fog to knock down fire fumes if possible.  
Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.  
Move containers away from the fire area if this can be done without risk.
- Special protective equipment for fire fighters : In confined space use self-contained breathing apparatus.  
Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.  
Standard EN 469 - Protective clothing for firefighters.  
Standard EN 659 - Protective gloves for firefighters.  
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

### SECTION 6: Accidental release measures

#### **6.1. Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel

- : Act in accordance with local emergency plan. Try to stop release. Evacuate area. Eliminate ignition sources. Ensure adequate air ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Stay upwind. See section 8 of the SDS for more information on personal protective equipment.

For emergency responders

- : Monitor concentration of released product. Consider the risk of potentially explosive atmospheres. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. See section 5.3 of the SDS for more information.

#### **6.2. Environmental precautions**

Try to stop release.

#### **6.3. Methods and material for containment and cleaning up**

Ventilate area.

#### **6.4. Reference to other sections**

See also sections 8 and 13.

### SECTION 7: Handling and storage

#### **7.1. Precautions for safe handling**

Safe use of the product

- : Assess the risk of potentially explosive atmospheres and the need for explosion-proof equipment. Ensure equipment is adequately earthed. Keep away from ignition sources (including static discharges). Consider the use of only non-sparking tools. Take precautionary measures against static discharge. Purge air from system before introducing gas. The product must be handled in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke while working with the product. Wash hands after use. Only experienced and properly instructed persons should handle gases under pressure. Wear personal protective equipment (See section 8). Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularly) checked for leaks before use. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Avoid suck back of water, acid and alkalis. Do not breathe gas. Avoid release of product into work area.

Safe handling of the gas receptacle

- : Refer to supplier's container handling instructions. Protect containers from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If the protection cap is too tight, remove it with adjustable wrench. Never insert sharp objects into the cavities of the cap, this can lead to damage to the valve and leakage. Open valve slowly to avoid pressure shock. If user experiences any difficulty operating valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water.

# Safety Data Sheet

## Propane-butane gas; LPG

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Reference number: RS-C3H8-C4H10-01

Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container.

Do not allow backfeed into the container. Suck back of water into the container must be prevented. Do not remove or deface labels provided by the supplier for the identification of the content of the container.

### **7.2. Conditions for safe storage, including any incompatibilities**

Segregate from oxidant gases and other oxidants in store.

All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere.

Observe all regulations and local requirements regarding storage of containers.

Containers should not be stored in conditions likely to encourage corrosion.

Container valve guards or caps should be in place.

Containers should be stored in the vertical position and properly secured to prevent them from falling over.

Stored containers should be periodically checked for general condition and leakage.

Keep container below 50°C in a well ventilated place.

Store containers in location free from fire risk and away from sources of heat and ignition.

Keep away from combustible materials.

### **7.3. Specific end use(s)**

None.

## **SECTION 8: Exposure controls/personal protection**

### **8.1. Control parameters**

OEL (Occupational Exposure Limits) : None available.

<b>Petroleum gases, liquefied (68476-85-7)</b>	
DNEL / DMEL : Derived no effect level (Workers)	
Long-term - systemic effects, inhalation	2,21 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	23,4 mg/ kg bw/day
DNEL / DMEL: Izvedena doza bez efekta (Population)	
Long-term - systemic effects, inhalation	0,0664 mg/m <sup>3</sup>

### **1,3 - Butadiene (106-99-0)**

DNEL / DMEL : Derived no effect level (Workers)

Long-term - systemic effects, inhalation	2,21 mg/m <sup>3</sup>
--	------------------------

DNEL / DMEL: Izvedena doza bez efekta (Population)

Long-term - systemic effects, inhalation	0,2652 mg/m <sup>3</sup>
--	--------------------------

PNEC (Predicted No-Effect Concentration) : None established.

### **8.2. Exposure controls**

#### **8.2.1. Appropriate engineering controls**

- Provide adequate general and local exhaust ventilation.
- Product to be handled in a closed system.
- Systems under pressure should be regularly checked for leakages.
- Ensure exposure is below occupational exposure limits (where available).
- Gas detectors should be used when flammable gases/vapours may be released.
- Consider the use of a work permit system e.g. for maintenance activities.

#### **8.2.2. Individual protection measures, e.g. personal protective equipment**

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected.

- Eye/face protection
  - : Wear goggles when transfilling or breaking transfer connections.  
Standard EN 166 - Personal eye-protection - specifications.  
[Standard EN ISO 16321-1 - Eye and face protection for occupational use Part 1: General requirements](#).
- Skin protection
  - Hand protection
    - : Wear working gloves when handling gas containers.  
Standard EN 388 - Protective gloves against mechanical risks, performance level 1 or higher.  
Recommended types include wrist gloves from leather or synthetic material with equivalent performance, fabric gloves, fabric gloves with leather palms.  
Wear cold insulating gloves when transfilling or breaking transfer connections.  
Standard EN 511 - Cold insulating gloves, performance level 1 or higher. Recommended types include insulated gauntlets or gloves specifically selected to prevent liquid penetration and ingress of cryogenic liquids and to provide mechanical resistance.
    - : Consider the use of flame resistant anti-static safety clothing.  
Standard EN ISO 14116 - Limited flame spread materials.  
Standard EN 1149-5 - Protective clothing: Electrostatic properties.  
Wear safety shoes while handling containers.  
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
  - Other
    - : Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres.  
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.  
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.  
Consult respiratory device supplier's product information for the selection of the appropriate device.
- Respiratory protection
  - : None in addition to the above sections.
- Thermal hazards

#### **8.2.3. Environmental exposure controls**

Refer to local regulations for restriction of emissions to the atmosphere.

See section 13 for specific methods for waste gas treatment.

### SECTION 9: Physical and chemical properties

#### **9.1. Information on basic physical and chemical properties**

Appearance

- Physical state at 20°C / 101.3kPa : Gas.  
- Colour : Colourless.

Odour

: Stenchant often added. Sweetish. Poor warning properties at low concentrations.

Melting point / Freezing point

: -187,6 °C / -138 °C

Boiling point

: -162 °C up to -0,5 °C

Flammability

: Extremely flammable gas.

Lower explosion limit

: 1,9 - 5,3 vol %

Upper explosion limit

: 8,5 - 15 vol %

Flash point

: < - 56 °C

Auto-ignition temperature

: 470 °C

Decomposition temperature

: 287 - 537 °C

pH

: Not applicable for gases and gas mixtures.

Viscosity, kinematic

: No reliable data available.

Water solubility [20°C]

: 0,024-0,061 g/L

Partition coefficient n-octanol/water (Log K<sub>ow</sub>)

: ≤ 2,8

Vapour pressure [20°C]

: 413 kPa

Vapour pressure [50°C]

: ≤ 1550 kPa

Density and/or relative density

: 0,56 g/cm<sup>3</sup>(15 °C)

Relative vapour density (air=1)

: >1.5

Particle characteristics

: Not applicable for gases and gas mixtures.

Nanoforms are not relevant for gases and gas mixtures.

#### **9.2. Other information**

##### **9.2.1. Information with regard to physical hazard classes**

Explosion limits : Not known.

Oxidising properties : No oxidising properties.

##### **9.2.2. Other safety characteristics**

Other data : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

### SECTION 10: Stability and reactivity

#### **10.1. Reactivity**

No reactivity hazard other than the effects described in sub-sections below.

#### **10.2. Chemical stability**

Stable under normal conditions.

#### **10.3. Possibility of hazardous reactions**

Can form explosive mixture with air. May react violently with oxidants.

#### **10.4. Conditions to avoid**

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
Avoid moisture in installation systems. (See Section 7.)

# Safety Data Sheet

## Propane-butane gas; LPG

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Reference number: RS-C3H8-C4H10-01

### 10.5. Incompatible materials

Air, Oxidisers.

For additional information on compatibility refer to ISO 11114.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11 : Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

<b>Acute toxicity</b>	: Toxicological effects not expected from this product if occupational exposure limit values are not exceeded.
<b>Skin corrosion/irritation</b>	: No known effects from this product.
<b>Serious eye damage/irritation</b>	: No known effects from this product.
<b>Respiratory or skin sensitisation</b>	: No known effects from this product.
<b>Germ cell mutagenicity</b>	: No known effects from this product.
<b>Carcinogenicity</b>	: No known effects from this product.
<b>Toxic for reproduction : Fertility</b>	: No known effects from this product.
<b>Toxic for reproduction : unborn child</b>	: No known effects from this product.
<b>STOT-single exposure</b>	: No known effects from this product.
<b>STOT-repeated exposure</b>	: No known effects from this product.
<b>Aspiration hazard</b>	: Not applicable for gases and gas mixtures.

### 11.2. Information on other hazards

Other information	: The substance/mixture has no endocrine disrupting properties.
-------------------	---

## SECTION 12: Ecological information

### 12.1. Toxicity

Assessment	: Classification criteria are not met.
------------	--

<b>Petroleum gases, liquefied (68476-85-7)</b>	
LC50 48h - Daphnia magna [mg/l]	14.22 - 69.43 mg/L
EC50 96h - Algae [mg/l]	7.71 - 16.5 mg/L
LC50 96 h - Fish [mg/l]	24.11 - 147.54 mg/L
<b>1,3 - Butadiene (106-99-0)</b>	
EC50 48h - Daphnia magna [mg/l]	24 - 33 mg/l
EC50 72h - Algae [mg/l]	11 - 33 mg/l
LC50 96 h - Fish [mg/l]	41.5 - 45 mg/L

### 12.2. Persistence and degradability

Assessment	: The substance is readily biodegradable. Unlikely to persist.
------------	--

### **12.3. Bioaccumulative potential**

Assessment : Not expected to bioaccumulate due to the low log  $K_{ow}$  ( $\log K_{ow} < 4$ ).  
See Section 9.

### **12.4. Mobility in soil**

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution.  
Partition into soil is unlikely.

### **12.5. Results of PBT and vPvB assessment**

Assessment : Not classified as PBT or vPvB.

### **12.6. Endocrine disrupting properties**

Assessment : The substance/mixture has no endocrine disrupting properties.

### **12.7. Other adverse effects**

Other adverse effects : Not classified as PMT or vPvM.

Effect on the ozone layer : No effect on the ozone layer.

Effect on global warming : When discharged in large quantities may contribute to the greenhouse effect.  
Contains greenhouse gases listed in Annex I of EU 2024/573.

## **SECTION 13: Disposal considerations**

### **13.1. Waste treatment methods**

Contact supplier if guidance is required. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Ensure that the emission levels from local regulations or operating permits are not exceeded. Refer to the EIGA code of practice Doc.30/21 "Disposal of Gases", downloadable at <http://www.eiga.eu> for more guidance on suitable disposal methods.

Do not discharge into any place where its accumulation could be dangerous.

Return unused product in original container to supplier.

: 16 05 04 \*: Gases in pressure containers (including halons) containing hazardous substances.

List of hazardous waste codes (from Commission Delegated Decision (EU) 2025/934 of 5 March 2025 amending Decision 2000/532/EC)

### **13.2. Additional information**

External treatment and disposal of waste should comply with applicable local and/or national regulations.

## **SECTION 14: Transport information**

### **14.1. UN number or ID number**

In accordance with ADR / RID / IMDG / IATA / ADN

UN-No. : 1965

### **14.2. UN proper shipping name**

**Transport by road/rail/inland waterways (ADR/RID/ADN)** : HYDROCARBON GAS MIXTURE, LIQUEFIED, N.O.S. (Butane n-, propane)

**Transport by air (ICAO-TI / IATA-DGR)** : Hydrocarbon gas mixture, liquefied, n.o.s. (Butane n-, propane)

**Transport by sea (IMDG)** : HYDROCARBON GAS MIXTURE, LIQUEFIED, N.O.S. (Butane n-, propane)

# Safety Data Sheet

## Propane-butane gas; LPG

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
 Reference number: RS-C3H8-C4H10-01

### **14.3. Transport hazard class(es)**



2.1 : Flammable gases.

#### **Transport by road/rail/inland waterways**

##### **(ADR/RID/ADN)**

Class	: 2
Classification code	: 2F
Hazard identification number	: 23
Tunnel Restriction	: B/D - Tank carriage: Passage forbidden through tunnels of category B, C, D and E. Other carriage: Passage forbidden through tunnels of category D and E

#### **Transport by air (ICAO-TI / IATA-DGR)**

Class / Div. (Sub. risk(s))	: 2.1
-----------------------------	-------

#### **Transport by sea (IMDG)**

Class / Div. (Sub. risk(s))	: 2.1
Emergency Schedule (EmS) - Fire	: F-D
Emergency Schedule (EmS) - Spillage	: S-U

### **14.4. Packing group**

Transport by road/rail/inland waterways (ADR/RID/ADN)	: Not applicable.
Transport by air (ICAO-TI / IATA-DGR)	: Not applicable.
Transport by sea (IMDG)	: Not applicable.

### **14.5. Environmental hazards**

Transport by road/rail/inland waterways (ADR/RID/ADN)	: None.
Transport by air (ICAO-TI / IATA-DGR)	: None.
Transport by sea (IMDG)	: None.

### **14.6. Special precautions for user**

#### **Packing Instruction(s)**

Transport by road/rail/inland waterways (ADR/RID/ADN)	: P200.
Transport by air (ICAO-TI / IATA-DGR)	
Passenger and Cargo Aircraft	: Forbidden.
Cargo Aircraft only	: 200.
Transport by sea (IMDG)	: P200.
Special transport precautions	<p>: Avoid transport on vehicles where the load space is not separated from the driver's compartment.</p> <p>Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.</p> <p>Before transporting product containers:</p> <ul style="list-style-type: none"> <li>- Ensure there is adequate ventilation.</li> <li>- Ensure that containers are firmly secured.</li> <li>- Ensure valve is closed and not leaking.</li> <li>- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.</li> <li>- Ensure valve protection device (where provided) is correctly fitted.</li> </ul>

# Safety Data Sheet

## Propane-butane gas; LPG

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Reference number: RS-C3H8-C4H10-01

### **14.7. Maritime transport in bulk according to IMO instruments**

Not applicable.

## **SECTION 15: Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### **RS Regulations**

Pravilnik o ograničenjima i zabranama proizvodnje, stavljanja : None.

u promet i korišćenja hemikalija ("Sl. glasnik RS", br. 90/13, 25/15, 2/16, 44/17, 36/18, 9/20, 57/22, 29/24 i 90/25)

Pravilnik o izvozu i uvozu određenih opasnih hemikalija („Sl. glasnik RS“ br. 93/23 i 78/25)

Zakon o kontroli opasnosti od velikih udesa koji uključuju opasne supstance ("Sl. glasnik RS", br. 94/24)

Pravilnik o Listi opasnih supstanci, vrstama i količinama opasnih supstanci i kriterijumima za razvijanje kompleksa u kompleksu nižeg reda i kompleksa višeg reda ("Sl. glasnik RS", br. 28/25)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	50	200

#### **EU Regulations**

Other information, restriction and prohibition regulations : None. Not listed on the PIC list (Regulation EU 649/2012).

Not listed on the POP list (Regulation EU 2019/1021).

Seveso Directive : 2012/18/EU (Seveso III) : Covered.

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	50	200

### **15.2. Chemical safety assessment**

A CSA has been carried out.

## **SECTION 16: Other information**

#### Indication of changes

- : In Section 1, the Safety Data Sheet is supplemented with information about details of the supplier of the safety data sheet.
- In Section 2, the Safety Data Sheet is supplemented with other hazards.
- In Section 8, the Safety Data Sheet is supplemented with information about personal protection.
- In Section 12, the Safety Data Sheet is supplemented with other adverse effects.
- In Section 13, the Safety Data Sheet is supplemented with information about waste treatment methods.
- In Section 15, the Safety Data Sheet is supplemented with regulatory information.

#### Abbreviations and acronyms

- : ADN - International Carriage of Dangerous Goods by Inland Waterways
- ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
- ATE - Acute Toxicity Estimate
- CAS - Chemical Abstract Service number
- CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
- CSA - Chemical Safety Assessment
- DNEL - Derived No Effect Levels

# Safety Data Sheet

## Propane-butane gas; LPG

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Reference number: RS-C3H8-C4H10-01

EINECS - European Inventory of Existing Commercial Chemical Substances  
 EC- European Community number  
 EIGA - European Industrial Gases Association  
 EN - European Standard  
 IATA - International Air Transport Association  
 ICAO - International Civil Aviation Organization  
 IMDG - International Maritime Dangerous Goods  
 IMO - International Maritime Organization  
 LC50 - Lethal Concentration to 50 % of a test population  
 LD50 - Lethal Dose 50%  
 LEL - Lower Explosive Limit  
 OEL - Occupational exposure limits  
 PBT - Persistent, Bioaccumulative and Toxic  
 PMT - Perzistentno, mobilno i toksično.  
 PNEC - Predicted No Effect Concentration  
 PPE - Personal Protection Equipment  
 PROC - Procesna kategorija (Process category).  
 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006  
 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail  
 RMM - Risk Management Measures  
 STOT - RE - Specific Target Organ Toxicity - Repeated Exposure  
 STOT- SE - Specific Target Organ Toxicity - Single Exposure  
 STEL - Short Term Exposure Limit  
 TWA - 8-hour total weight average  
 UEL - Upper explosive limit  
 UFI - Unique Formula Identifier  
 UN - United Nations  
 vPvB - Very Persistent and Very Bioaccumulative  
 vPvM - veoma perzistentno i veoma mobilno.  
 WGK - Water Hazard Class  
 Training advice : Receptacle under pressure. Ensure operators understand the flammability hazard.  
 Further information : Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).  
 Key literature references and sources of data are maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at <http://www.eiga.eu>

Full text of H- and EUH-statements	
Flam. Gas 1A	Flammable gases, Category 1A
H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
Press. Gas (Liq.)	Gases under pressure : Liquefied gas

DISCLAIMER OF LIABILITY : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.  
 Details given in this document are believed to be correct at the time of going to press.  
 Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

**End of document**